



## DESCRIPTION & ADVANTAGES

### ARTISTIC SPECIALTIES CANVAS SATIN

---

#### TURBO CANVAS SOLVENT 400

**satin 3378** 400 g/m<sup>2</sup>

Satin coated canvas with a 1:1 weave structure for solvent inks. Due to the special coating, the Turbo Canvas allows heavy ink loads and uniform prints, even in critical dark tones: with optimised ink fixation. The coated surface is water-repellent and offers a good light-stability.

#### **Advantages**

- Best cost : performance ratio
- Real cotton / polyester canvas (1:1 structure)
- Water-resistant, satin finish
- Flexible finishing for ideal performance during stretching

## GENERAL TIPS & STORAGE

The converting and storage should take place in a climate from 35 to 65% to relative humidity at a temperature from 10 to 30°C. Due to the natural components of the material it tends to curl when relative humidity is quite high, what can cause print head damages. Therefore we recommend to only move the material out of its original packaging when printing immediately. After the printing process remove the material back to its original packaging again. It is always recommended that cotton gloves be used when handling InkJet coated materials to avoid fingerprints.

[MediaSafetyDataSheet \(pdf\)](#)

## SIZES, APPLICATIONS, PROPERTIES

Finished Rolls

Width	Length	Width	Length	Core	No. rolls / pallet	Min. quantity / order	No. rolls / box
36.0 "	49.2 ´	91.4 cm	15.0 m	3 "ø	30	10	1
42.0 "	49.2 ´	106.7 cm	15.0 m	3 "ø	30	10	1
54.0 "	49.2 ´	137.2 cm	15.0 m	3 "ø	30	10	1
60.0 "	49.2 ´	152.4 cm	15.0 m	3 "ø	30	10	1

### Mill Reels

Width	Length	Width	Length	Core	No. rolls / pallet	Min. quantity / order	No. rolls / box
42.5 "	2,460.6 ´	108.0 cm	750.0 m	3 "ø	1	1	
54.3 "	2,460.6 ´	138.0 cm	750.0 m	3 "ø	1	1	
60.6 "	2,460.6 ´	154.0 cm	750.0 m	3 "ø	1	1	

### Applications



### Print technologies



### Properties



Other sizes may be available upon request.

### physical properties

#### satín 3378 400 g/m<sup>2</sup>

Weight (Total) [gsm]	400	ISO 536
Thickness (total) [microns]	470	ISO 534
Whiteness (ISO) [%]	75	ISO 2470-1
Gloss (60°)	5	ISO 2813
Weave structure	1:1	
Base	78% Cotton / 22% Polyester	

### PRINTER COMPATIBILITIES

Printer	3378
Hewlett Packard DJ 8000S / 9000S / 10000S	😊😊
Hewlett Packard DJ L65500 Latex ink	😊😊
Hewlett Packard DJ L25500 / 26500 / 28500 - Latex 260 / 280	😊😊
Hewlett Packard Scitex LX 600	😊😊
Hewlett Packard Scitex LX 800 / LX 820 / LX 850	😊😊
Epson Stylus Pro GS6000 UltraChrome GS	😊😊😊
Roland SolJet SJ540 / SC540 SJ 740 / SC740	😊😊😊
Roland VersaCAMM SP-300i / SP-540i	😊😊😊
Roland VersaCAMM VP-300i / VP-540i	😊😊😊
Roland VS 540 / VS 640	😊😊😊
Mimaki JV 33 / JV34 - 260	😊😊
Mimaki JV400SUV Serie	😊😊😊
Mutoh ValueJet 1204 / 1304 /1614	😊😊
Zünd UVjet 215 C	😊😊
swissQprint Oryx	😊😊😊
swissQprint Impala	😊😊😊
Last update	1/4/2016
Legend	
Excellent	😊😊😊
Good	😊😊
Fair	😊

Datasheet

Online Datasheet **satin 3378** 400 g/m<sup>2</sup> 