

TECHNICAL DATA

	AT60n	AT65	AT75.1
Physical Properties			
Application	Clear Film Transfer Tape	Clear Film Transfer Tape	Clear Film Transfer Tape
Color	Transparent	Transparent	Transparent
Adhesive	Acrylic	Acrylic	Modified Polyacrylate
Caliper	Embossed Polypropylene	Embossed Polypropylene	Embossed HOPE
	3.7 mil (94 µm)	3.7 mil (94 µm)	4.25 mil (108 µm)
Tack Level	Low	Medium	High
Adhesion to Steel	1 - 3 oz/in (1 - 3 N/100mm)	2 - 6 oz/in (2 - 7 N/100mm)	5 - 9 oz/in (5 - 10 N/100mm)
Die-Cut Graphics Size	Transferring large letters/graphics and protecting digital prints	Small to Medium size. Ideal for small and fine detail cut graphics and vinyl film w/tight release liners	Small to Medium size. Ideal for difficult to transfer films, textured and matte finish films
Tensile	25 MPa (3600 psi)	25 MPa (3600 psi)	14 MPa (2000 psi)
Elongation	750%	750%	300-500%
Wet Application Installation	Moderate	Excellent	Excellent
Compatible	Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
Shelf Life	1 Year	1 Year	1 Year

Disclaimer

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.