

PRODUCT DESCRIPTION

4885 is an application tape with a off-white/translucent premium or heavyweight saturated paper with super high tack rubber adhesive, designed for very small lettering and graphics and hard-to-lift films. Exceptional resistance to abrasion and moisture.

Adhesive	Rubber-based
Color	Off-white/Translucent
Thickness tape	100-120 microns
Thickness tape + adhesive	135-155 microns
Adhesion to steel*	5,5+N/25mm
Tensile	83 N/25mm
Elongation	12%
Tear resistance	70-80 grams
Shelf life**	1 year

* Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture

** Stored at 22°C /50-55% RH

FEATURES & BENEFITS

- Transfer of hard-to-lift textured vinyls, etched glass vinyls and small thermal die cut graphics.
- Very small lettering and fine detail plotter-cut graphics.

APPLICATIONS

- Small graphics
- Thermal die-cut graphics
- Designed for highly textured surfaces and four color UV clear coats.

Important notice: All RTape products are subject to continuous quality control throughout the manufacturing process and are warranted to be free from manufacturing defects. RTape stands behind its products and will replace or credit any defective material. Because RTape products are used for a variety of applications, the purchaser is responsible for determining the suitability and performance of this product for their specific purpose, prior to use and the purchaser shall assume all risks regarding such use.

RTape Corp.
6 Ingersoll Road, South Plainfield, NJ 07080
Tel: 908-753-5570 Fax: 908-753-5014
sales@rtape.com
www.rtape.com

Represented in Europe by:
the iC GROUP
Groendreef 35, 9880 Aalter,
Belgium Tel: +32 9 216 67 00
info@theicgroup.eu
www.theicgroup.eu