

TECHNICAL DATA SHEET

ITEM IK12552

Description	Clear 125 micron PET base film with a toner receptive coating on one side for laser and dry toner printing as well as HP Indigo printing, with a backing paper, with excellent print adhesion and with vivid and dense colors		
Sheet size	330 x 480 mm		
PRODUCT SPECIFICATIONS			
	UNIT	VALUE	STANDARDS
Base film thickness	micron	125 ±3	Thwing-Albert tester
Surface	Gloss		
Tensile strength	Kgf/mm ² MD	≤22	ASTM D882-83
	Kgf/mm ² TD	≤19	
Shrinkage	% MD	≤0.5	Dry air at 150°C
	% TD	≤1.5	
Processing recommendations	Substrates should be climatized at room temperature 24 h before printing		
	Print at roomtemperature with relative humidity between 50-60%		
Recommended storage	Temperature 10-30°, relative humidity 50-60%		
Shelf Life	1 year in recommended storage conditions		
<p>This specification does not absolve users from performing their own tests. The values indicated are the results of laboratory tests and under no circumstances they must be taken to an absolute reference; therefore they cannot be considered as a warranty or a commitment. The user is solely responsible for all decisions about the use of the material. Isita shall not be liable for any direct or indirect damages resulting from inappropriate use of the information contained in data sheets.</p>			