

## TriSolv PrimeArt Paper SA 275

— glossy 3685 - 275 g/m<sup>2</sup>

The self-adhesive TriSolv member of the PrimeArt family has a thicker liner which is ideal for use on cutting plotters. The waterbased acrylic adhesive adheres to virtually all clean, smooth surfaces, making it possible to produce individually designed stickers and labels.

### Applications

- Adhesion on stands
- High quality photo reproduction
- Indoor signs
- Indoor adverts

### Advantages

- Water-repellent surface
- Premium poster paper
- Excellent colours
- High colour saturation saves up to 30 % ink
- Perfect for eco-solvent inks
- Optimised for use on cutting plotters

## TriSolv PrimeArt Paper SA 275

— glossy 3685 - 275 g/m<sup>2</sup>

### List of Printers

Printer	Ink	Quality
Hewlett Packard Latex 310 / 330 / 360 / 3000	Inkjet with IR / Latex Ink	Excellent
Hewlett Packard Latex 280 / 820 / 850	Inkjet with IR / Latex Ink	Excellent
ColorSpan Display Maker 72 UVR	Inkjet with UV Curable Ink	Excellent
Mimaki JV400SUV Serie	Inkjet mit Solvent-UV	Excellent
Océ Display Graphics Systems / Rastergraphics Arizona 500	Inkjet with Solvent Ink	Excellent
Seiko SII Colorpainter 64S / 100S / W-54s/W-64s / H2-74s/H2-104s	Inkjet with Eco Solvent	Excellent
Zünd UVjet 215 C	Inkjet with UV Curable Ink	Excellent
Zünd UVjet 250	Inkjet with UV Curable Ink	Excellent
Durst Rho 160	Inkjet with UV Curable Ink	Excellent
Epson Stylus Pro GS6000 UltraChrome GS	Inkjet with Eco Solvent	Good
Roland SolJet SJ540 / SC540 SJ 740 / SC740	Inkjet with Eco Solvent	Good
Roland SC-500 Permasol S	Inkjet with Solvent Ink	Good
Roland VersaCAMM SP-300i / SP-540i	Inkjet with Eco Solvent	Good
Roland VersaCAMM VP-300i / VP-540i	Inkjet with Eco Solvent	Good
Roland VS 540 / VS 640	Inkjet with Eco Solvent	Good
Roland SolJET PRO4 XR-640	Inkjet with Solvent Ink	Good
Mimaki JV-3 160S, 250	Inkjet with Solvent Ink	Good
Mimaki CJV 30	Inkjet with Eco Solvent	Good
Mimaki JV 400 -130LX /-160LX	Inkjet with IR / Latex Ink	Good
Mutoh Toucan	Inkjet with Solvent Ink	Good
Mutoh ValueJet 1204 / 1304 /1614	Inkjet with Eco Solvent	Good
Océ CS6060	Inkjet with Eco Solvent	Good
Océ CS9360 / CS935	Inkjet with Eco Solvent	Good
Ricoh PRO-L4160-4C	Inkjet with IR / Latex Ink	Good
Mutoh Rockhopper II 50", 64", 87"	Inkjet with Eco Solvent	Fair

Last update: 26.09.2014

## TriSolv PrimeArt Paper SA 275

— glossy 3685 - 275 g/m<sup>2</sup>

### Physical Properties

Weight (Total) [gsm]	275	ISO 536
Thickness (total) [microns]	280	ISO 534
Chromaticity (D50 / 2°)	L* 94.0 a* 0.8 b* -3.7	ISO 13655, M0
Adhesion Strength Glas [N/25mm]	20	FTM 1 (24h)
Adhesion strength on V2A [N/25mm]	25	FTM 1 (24h)
Adhesion strength on Forex [N/25mm]	20	FTM 1 (24h)
Base	TriSolv PrimeArt Paper 135 glossy 3684	

### General tips & storage

- Please note when printing with any of the 300 series HP Latex printer, to print roll to roll!
- The ink amounts must be adjusted to the paper. Please reduce the single colors cyan, magenta, yellow and black (ink restrictions) and shorten the maximum amount of ink (ink limit). This will help your costs on inks and improve your drying performance.
- Please follow the recommendations of the printer and ink manufacturer. The temperature for preheating and drying the media should be checked previously to make sure you will achieve desired results.
- To maintain the high quality of the paper, it should be stored and converted in a climate of 30 - 65 % relative humidity and at a temperature of 10 - 30 °C (50 - 86 °F).
- Latex / IR hardening ink is not fully water-resistant.

[Recommendations of use \(pdf\)](#)

The values provided on this datasheet are only for orientation.

Before using our media please check its compatibility for your printer and intended application. Technical specifications are subject to change, therefore we do not take responsibility for any misprints resulting from technically modified inks and/or printers.