



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 90 g/m<sup>2</sup>

|                           |     |                  |           |                    |
|---------------------------|-----|------------------|-----------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   | <b>90 ± 3.0</b>    |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   | <b>98 ± 4</b>      |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>130 ± 30</b>    |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>70 ± 15</b>     |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  | <b>105 ± 25</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min 92.0</b>    |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper.  
Production processes certified according to ISO 9001, 14001 and 18001.

SIGINIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

10.12.2007



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 100 g/m<sup>2</sup>

|                           |     |                  |           |                    |
|---------------------------|-----|------------------|-----------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   | <b>100 ± 4.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   | <b>106 ± 4</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>160 ± 30</b>    |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>90 ± 25</b>     |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  | <b>105 ± 25</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min 93.0</b>    |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper.  
Production processes certified according to ISO 9001, 14001 and 18001.

SIGINIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

10.12.2007



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 120 g/m<sup>2</sup>

|                           |     |                  |           |                    |
|---------------------------|-----|------------------|-----------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   | <b>120 ± 4.5</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   | <b>126 ± 4</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>245 ± 30</b>    |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>130 ± 25</b>    |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  | <b>105 ± 25</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min 95.0</b>    |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper.  
Production processes certified according to ISO 9001, 14001 and 18001.

SIGINIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

10.12.2007



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



### Technical Data: Color Copy 160 g/m<sup>2</sup>

|                           |     |                  |           |                 |              |
|---------------------------|-----|------------------|-----------|-----------------|--------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   | <b>160</b>      | <b>± 6.0</b> |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   | <b>166</b>      | <b>± 6</b>   |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>490</b>      | <b>± 40</b>  |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>250</b>      | <b>± 30</b>  |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  | <b>105</b>      | <b>± 25</b>  |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min 97.0</b> |              |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  | <b>110.0</b>    | <b>± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 | <b>160</b>      | <b>± 3.0</b> |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper.  
Production processes certified according to ISO 9001, 14001 and 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

10.12.2007



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 200 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>200 ± 6.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>200 ± 7</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>620</b>         |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>330</b>         |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>160 ± 40</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>98.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, 14001 and 18001.

SIGINIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 220 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>220 ± 6.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>220 ± 7</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>800</b>         |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>400</b>         |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>160 ± 40</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>99.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper.  
Production processes certified according to ISO 9001, 14001 and 18001.

SIGINIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 250 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>250 ± 7.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>245 ± 8</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>900</b>         |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>500</b>         |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>160 ± 40</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>99.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, 14001 and 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 280 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>280 ± 8.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>275 ± 9</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>1300</b>        |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>700</b>         |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>140 ± 40</b>    |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>99.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, 14001 and 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 300 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>300 ± 8.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>305 ± 9</b>     |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>1600</b>        |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>800</b>         |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>90 ± 30</b>     |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>99.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, 14001 and 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008



Color Copy - the leading paper guarantees you needle-sharp printouts and brilliant colour reproduction, especially with digital colour laser printing. It is perfectly suitable for documents such as presentations, direct mailings, manuals, corporate plans, business cards and envelopes.



**Technical Data:** Color Copy 350 g/m<sup>2</sup>

|                           |     |                  |           |            |                    |
|---------------------------|-----|------------------|-----------|------------|--------------------|
| <b>Grammage</b>           |     | g/m <sup>2</sup> | ISO 536   |            | <b>350 ± 8.0</b>   |
| <b>Caliper</b>            |     | mm/1000          | ISO 534   |            | <b>350 ± 10</b>    |
| <b>Stiffness L&amp;W</b>  | MD  | mN               | ISO 2493  | <b>min</b> | <b>2000</b>        |
| <b>Stiffness L&amp;W</b>  | CD  | mN               | ISO 2493  | <b>min</b> | <b>1000</b>        |
| <b>Smoothness Bekk</b>    |     | sec              | ISO 5627  |            | <b>90 ± 30</b>     |
| <b>Opacity</b>            |     | %                | ISO 2471  | <b>min</b> | <b>99.0</b>        |
| <b>Brightness with UV</b> | D65 | %                | ISO 2470  |            | <b>110.0 ± 1.5</b> |
| <b>CIE Whiteness</b>      |     |                  | ISO 11475 |            | <b>160 ± 3.0</b>   |

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and ISO 9706, requirements for permanence for paper. Production processes certified according to ISO 9001, 14001 and 18001.

SIGNIFICANCE OF VALUES: 2 SIGMA

TECHNICAL CUSTOMER SERVICE

09.01.2008