

INSTRUCCIONES DE TRABAJO	
Versión nº: 2	Fecha de revisión: Septiembre 2011
IDT-605: Fichas técnicas de producto	



## TECHNICAL DATA

# PRESSURE SENSITIVE PS-14

Base material : Rubber resin  
 Colour : Amber  
 Shelf Life : Maximum 3 Years, when stored in dark area, at temperature of 10°C to 30°C.  
 Suggested uses : On most clean and smooth surfaces. (Except any kind of plastifying)

### Adhesives Properties

Peel Strength 180° :

Curing time 20 minutes	Minimum 8 N/cm	Test method : FINAT ; FTM 1
	Average 15 N/cm	

Curing time 24 hours	Minimum 10 N/cm	Test method : FINAT ; FTM 1
	Average 17 N/cm	

Static Shear Strength:	≥ 7 days	Test method : FINAT ; FTM 8
------------------------	----------	-----------------------------

Softening Point:	≥ 90°C	Test method : ASTM D-816
------------------	--------	--------------------------

FINAT: Fédération Internationale des fabricants transformateurs d'Adhésifs et Thermocollants. ASTM: American Society for Testing and Materials.  
Tested on: Anodized aluminium plates under laboratory conditions. (23°C ± 2 and 60 ± 10 % R.H.)

### Resistance properties

Oxidation	Poor
Plastifying, oils	Poor
High relative humidity	Poor
Polar solvents (M.E.K. etc.)	Poor
Non-polar solvents (gasoline, etc.)	Suitable
Migration	Poor
High temperature	Suitable
Low temperature	Suitable
U.V. radiation	Poor
Temperature Range:	-15°C to +90°C (Depending on loading and Relative Humidity).

### General Directions for Use

Application temperature range: 20°C to 30°C.

Degrease the substrate with e.g. alcohol or spirit. (The substrate must be free of grease, moisture, dust, silicones, etc.).

Remove the protective paper and press the tape firmly into contact with the substrate, with special attention to the edges.

Preferably, allow substrate and pressure sensitive tape to stand for 24 hours after applying load.

\* Internal norm of VESA

The information included in this Technical Sheet is based on reliable test and trials. Average value as a reference only, not a nominal specification. Given the diversity of uses of our products we advise our customers to assure themselves that the product meets the requirements of their application. The responsibility for the application and use of the product remains with the customer.

Elaborado: J.C. Lima

Revisado: E. Duet

Autorizado: J. Jacobs

Fecha: 11.10.11

ANEXO: IDT – 605-B

FTP 500 Versión 5